

Weighbridge Indicator for Digital and Analog Load Cells

FEATURES

- Supports digital and analog load cells
- Easy calibration when used with digital load cells
- Easy digital corner compensation
- Elaborated diagnostics of digital weighbridge load cells
- Easy service and maintenance
- Large, 16-character LCD display
- 27-key keyboard featuring alphanumeric and function keys
- Up to three serial ports with printing and networking
- Analog output for PLC interface (optional)
- Two opto-isolated weight setpoints
- Alibi (Flash) memory for transaction records
- Real-time clock
- Stainless steel enclosure (IP65), aluminum enclosure (IP40)
- Weighing and counting operating modes
- OIML R-76 approved to 10,000d
- Dual scale operation (one digital, one analog)
- 4 programmable ticket formats
- **Optional**
 - Analog output for PLC interface
 - Second RS232 print port (for aluminum version only)
 - PS2 keyboard interface (for aluminum version only)

APPLICATIONS

- Weighbridges
- Inventory control
- Industrial weighing systems
- Bench, floor, and counting scales



DESCRIPTION

The Model VT300D is a powerful alphanumeric terminal, designed for digital and analog weighbridges, inventory control, and other demanding weighing applications.

The extended keyboard includes alphanumeric and function keys for easy data entry and setup.

A 16-character dot-matrix LCD display supports the required user interface in complex industrial applications.

Using a weighing system that includes the Model VT 300D together with VPG Transducers digital load cells (DSC, SCC, SBC and MDBD) enables very easy installation, calibration, corner compensation, maintenance and diagnostics of the system.

The Model VT 300D's software manages various transactions allowing choices of customer, material type, or truck identification. Records of all activities are maintained in the indicator's memory and made available for computer reporting. Printable tickets and reports are easily formatted and edited.


The Model VT 300D can support one digital load cells weighbridge and one analog load cell weighbridge at same time.

Enclosure selections include tilted, wall-mount, and desktop.

See next page for further data.

Weighbridge Indicator for Digital and Analog Load Cells

CONFIGURATION



SPECIFICATIONS

PERFORMANCE

Analog Load Cell Interface Performance

Resolution

Selectable up to 990,000 dd

Conversion Speed

3–228 samples per second (selectable)

Sensitivity

0.4 $\mu\text{V}/\text{Vsi}$ for approved scales,
0.1 $\mu\text{V}/\text{Vsi}$ for non-approved scales

Full Scale Range

–0.25 to 1.75 mV/V or –0.25 to 3.75 mV/V

Linearity

0.002% of full scale

Long-Term Stability

0.005% of full scale per year

Excitation

+5V alternating polarity or +5 VDC (selectable), with sense (6 wires)

Number of cells

Up to 10; 350 Ω load cells

Filter

FIR automatically adjusted to conversion speed, rolling average.

Offset Drift

≤ 2 ppm/ $^{\circ}\text{C}$

Span Drift

≤ 2 ppm/ $^{\circ}\text{C}$

A/D Converter Type

Sigma-Delta, ratiometric, 550,000 internal counts

Digital Load Cell Interface Performance

Resolution

Selectable up to 990,000 dd

Update Rate

25 updates per second

Supply to Load Cell

14–18 VDC; 1.5A (Standard 15V)

Number of Cells

Up to 12

Compatible Load Cells

DSC, SCC, SBC, MDBD

General Performance

Count By

x1, x2, x5, x10, x50, x100, x200

Decimal Point

Between any digits of the weight display

Calibration Methods

Dead load and span, or data sheets calibration, via the mV/V output values of the load cell. Digital corner correction. Digital default calibration.

Weighing Functions

Automatic zero tracking, no motion detection, auto-zero on power-up, zero tare, preset tare, net mode, multiple test functions.

Memory Allocation

Calibration data EEPROM, flash tally-roll (Alibi) memory capable of 10,000 weight registrations, 250 records database (trucks). Stores the digital load cell performance and calibration data.

Piece Counting Mode

Real-Time Clock

Weighbridge Indicator for Digital and Analog Load Cells

ENVIRONMENTAL**Operating Temperature**

-10°C to +40°C [14°F to 104°F]

Storage Temperature

-10°C to +70°C [-4°F to 158°F]

Relative Humidity

40–90% RH, non-condensing

DISPLAY AND KEYBOARD**Display**

16-character, LCD, backlit

Digital Height

14.5 mm

Status Enunciators

No motion, zero, tare in use, net, scale in operation (#1 or #2 or sum # 1+2, if second scale connected), piece counting mode

Weight Digits

4, 5 or 6 (setup selectable)

Keyboard

Pseudo-alphanumeric, 27 keys, with tactile feedback

ELECTRICAL**Voltage**

85–265 VAC

Current

500 mA

ISOLATED ANALOG OUTPUT (OPTIONAL)**Resolution**

16 bit DAC

Voltage Output

0.02–10V

Current

0–20 mA or 4–20 mA

Linearity

0.01% of full scale

Thermal Stability

50 ppm /°C typical

INPUTS AND OUTPUTS**(x1) Logic Input**

9–24 VDC, negative common, opto-isolated to 2.5 kV

(x2) Logic Output

24 VDC ±10%, positive common, max current 100 mA, opto-isolated to 2.5 kV.

SERIAL COMMUNICATION**Serial Output #1**

RS232 Full duplex, programmable

Baud Rate

1200–9600 baud, full duplex

Applications

Printer output, weight output

Serial Output #2

RS-485 setup programmable

Baud Rate

2400–115200 baud, half duplex

Applications

EDP output, master-slave protocols, continuous output, remote printer and digital load cell communication.

Serial Output #3

RS232PRN' programmable

Baud Rate

2400–115200

Applications

Printer output

ENCLOSURE

Stainless Steel Enclosure

Dimensions

252 x 152 x 62 mm L x H x D

Mounting

Wall and tilt mount

Protection

IP65

Wiring Connections

Cable glands

Aluminum Enclosure

Dimensions

194 x 100 x 107 mm L x H x D

Mounting

Desktop

Protection

IP40

Wiring Connections

D-sub connectors

APPROVALS (ACCURACY CLASS III)**OIML R-76**10,000d single or dual interval
EU-type approval no. 0200-NAWI-03996

VPG Transducers is continually seeking to improve product quality and performance.
Specifications may change accordingly.



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.