



## Automatic film applicators **ZAA2300**

---

### Automatic Film Applicator

---




#### Ease of use

Multifunctional use with reversible, double-sided glass plate (glass/printing blanket), easy to turn over or to change with an adjustable application area.



#### User Experience

Automatic laboratory equipment for accurate and reproducible results of the application of coating materials, adhesives, and similar products with almost all film applicators.



#### Versatility

Functional design with adjustable application area with moveable start and stop positions.



## Processing Unit / Sensor

<b>Application length</b>	Application length: up to 400 mm (15.75")
<b>Application width</b>	Application width: up to 300 mm (11.81")
<b>Weight</b>	20 kg (44.1 lbs) glass plate only: 6.4 kg (14.1 lbs)
<b>Battery</b>	Power supply: 100 V - 240 V, 50 Hz - 60 Hz
<b>Operating Temperature</b>	Ambient conditions for the operation: Temperature range: 5°C to +45°C (41 °F to 113 °F) Relative humidity: 20% to 80%, no condensation
<b>Temperature range</b>	Ambient conditions for operation: 5°C to +45°C (41 °F to 113 °F)
<b>Relative humidity</b>	20% to 80%, no condensation
<b>Drawing speed</b>	ZAA2300 1mm/s ZAA2300.F 2.5mm ZAA2300.FF 5mm/s1mm/s
<b>Resolution</b>	Depending on version: either 1 mm/s, 2.5 mm/s or 5 mm/s

SWISS  MADE

Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.

[www.screeningeagle.com](http://www.screeningeagle.com)

[Request a quote](#)