

# FG-EVAC-500\_AP PUBLIC ADDRESS & VOICE ALARM SYSTEM



## PRODUCT OVERVIEW

The **FG-EVAC-500\_AP** is a compact EN 54-16 certified public address and voice alarm system that ensures a fast, safe and controlled emergency evacuation. **FG-EVAC-500\_AP** is the most versatile and cost effective PA/VA system, thanks to its cutting-edge features, excellent audio quality and flexibility in minimum space. It has 2 class D amplifiers, 6 zones, 3 audio inputs, 6x6 audio matrix, DSP and LCD display. The system can be configured without software or PC, thanks to the Plug & Set mode for PA/VA. Audio inputs and automatic mixing allow high versatility for PA use in small installations. **FG-EVAC-500\_AP** has an EN 54-4 battery charger and can operate with one 12V battery. This feature and its advanced power saving control reduce maintenance costs to the maximum. A Wall & Rack innovative design makes **FG-EVAC-500\_AP** suitable for wall mounting and rack integration.




## Features

- 3 audio inputs.
- Up to 8 MPS-8Z multizone micropophones or VAP-1 panels connected with CAT5 UTP cable.
- 2 class D amplifiers with two configurations for 100V/70V lines up to 500W.
- Digital audio matrix 6x6, expandable.
- 4 pre-amp outputs for external PA amplifiers connection.
- DSP: 3/7-band input/output parametric equalizer, loudness, Ravel sound enhancer, independent volume control per each input and output master.
- Access control by LCD display.
- Control for up to 16 Ravel AT6 attenuators.
- 8+2 GPIO ports, supervised for integration with Fire Alarm Control Panel.

## Voice Alarm / Emergency Features

- Certified under EN 54-16, EN 54-4 and EN 60849 standards.
- Failure detection and indication in all emergency functions.
- Fire Alarm Control Panel integration.
- Double player for pre-recorded evacuation messages.
- Manual control of emergency states with access control.
- Emergency log.
- Loudspeaker lines supervision.
- Line terminator without return for supervision.
- Backup amplifier included.
- 10 minutes storage for pre-recorded messages.

MODEL	DESCRIPTION
FG-EVAC-500_AP	Public Address & Voice Alarm System



## Technical Specification

Power supply :	100 - 240V~ 50/60Hz
Power consumption :	350W max / 100W at 1/8 output power
Frequency response :	80 – 20000Hz +/-1dB
Signal to noise ratio :	SNR~95dB, A-weighted
Distorsion factor :	<0.1% according to IEC 60268
Gain adjustment per channel :	-100dB +10dB, 1dB steps
DSP :	Integrated - 48 kHz, 24 bits - 344 MIPS
BGM audio inputs :	1 x balanced audio 1 Vrms. 10 K $\Omega$ , 3 Pin, Euroblock type
Priority audio inputs :	2 x balanced audio 1 Vrms. 10 K $\Omega$ , 4 Pin, Euroblock type (GPIO)
General control (GPIO) :	2 x control I/O, 0-5 V, 100 $\Omega$ , in PRIO audio inputs
Ravel ACSI Bus :	1 x balanced audio 1 Vrms. 10 K $\Omega$ , RJ-45 female, total 800m / 2624.7ft
ACSI-Link connectivity :	2 x balanced audio 1 Vrms. 10 K $\Omega$ , RJ-45 female, total 800m / 2624.7ft
Pre-amp audio outputs :	4 x balanced audio 1 Vrms. 100 $\Omega$ , 3 Pin, Euroblock type
Attenuators control :	6 x override 24V DC, 6 x 30mA, 2 Pin, Euroblock type (4 pin connector)
Emergency control inputs :	8 x 0 - 5V DC, monitored inputs, 2 Pin, Euroblock type (4 pin connector)
Emergency control outputs :	2 x contact closure output, NO, max 60V DC 130mA, 2 Pin, Euroblock type (4 pin connector)
Virtual matrix :	15 x 24 maximum
Amplifier :	2 x 500W D class (250Wrms x 2) @ 70 / 100V. Min load 20 $\Omega$
Backup amplifiers :	1 backup amplifier with automatic priority according to EN 54-16
Speaker line outputs :	6 x 100V audio. Min. impedance: 20 $\Omega$ 500W (outputs 1 and 2), 80 $\Omega$ 120W (rest), 2 Pin, Euroblock type
Output power :	500 W according to EN60065. 200 Wrms according to EN 54-16
Protection :	Over-temperature, infrasonic, short circuit, slow start-up, overload
Emergency power :	181x76x167mm battery housing, up to 22Ah
Battery charger :	Integrated, smart charging up to 3 amperes
Display :	Backlit LCD 2 rows x 16 characters
Operation conditions :	-5 $^{\circ}$ C to +45 $^{\circ}$ C / 23 $^{\circ}$ F to 113 $^{\circ}$ F 5% to 95% relative humidity (without condensation)
Finish :	Materials : Fe y AL
Colours :	RAL7016 and RAL9005
Weight :	7.5 Kg / 15.76 lb
Dimensions (W x H x D) :	453mm x 88mm x 455mm / 18.2" x 3.46" x 18"
Accessories :	Male Euroblock connectors, installation screws, 4 x rubber foot



“ Fireguard aims to be customer’s first choice to safeguard from hazardous fires, by designing, developing the latest technology products with high quality and reliability.”

### FIREGUARD GLOBAL LTD.

Tel: 00-44-8450751042

Fax: 00-44-8459751043

Email: [Info@Fireguard-Uk.com](mailto:Info@Fireguard-Uk.com)

[www.fireguard-Uk.com](http://www.fireguard-Uk.com)



Unit 11 · Chancel Industrial Estate · Newhall Street  
Willenhall · WV13 1NX · United Kingdom



FS546607

