




Pneumatic rotary gear pump for the transfer of low viscosity oil, antifreeze, diesel, water.

Pump body in brass (art. no. 6559) or in stainless steel (art. no. 1058), gears in Kevlar, gaskets in Viton® and pump shaft in stainless steel.



Art. no.	Compressed air supply	Outlet pressure	Delivery	Connections	Weight	Dimensions (LxWxH) (mm)
6559	4 bar	4 bar	10.5 l/min	3/8" BSP (F)	1.5 kg	165x160x80
1058	4 bar	4 bar	10.5 l/min	3/8" BSP (F)	1.5 kg	165x160x80



Electric gear pump for an intermittent use, for the transfer of low viscosity oil (Oil), antifreeze (A), diesel (D), water (W).

Protection category IP55. Pump body in brass, gears in bronze and pump shaft in stainless steel.

Electric cable and crocodile clamps not included.



Art. no.	Voltage	Current drain	Suitable Fluids	Delivery	Outlet pressure	Connections	Weight	Dimensions (LxWxH) (mm)
6302	12 VDC	6 A	A - D - W	15 l/min	2 bar	3/8" BSP (F)	1.5 kg	165x160x80
6303		5 A	Oil	1 l/min	4 bar		2.5 kg	165x166x80
6304	24 VDC	3 A	A - D - W	15 l/min	2 bar		1.5 kg	165x160x80
6305	12 VDC	11 A	Oil	6 l/min	4 bar		4 kg	180x230x83
6308	24 VDC	3 A	Oil	1 l/min	4 bar		2.5 kg	165x166x80
6309		6 A	Oil	6 l/min	4 bar		4 kg	180x230x83

Electric gear pump for an intermittent use, for the transfer of low viscosity oil (Oil), antifreeze (A), diesel (D), water (W).

Pump body in brass, gears in bronze and pump shaft in stainless steel. With metal cover, ON/OFF switch and 1 m - cable with alligator clamps for battery connection. Protection category IP55.



Art. no.	Voltage	Current drain	Suitable Fluids	Delivery	Outlet pressure	Connections	Weight	Dimensions (LxWxH) (mm)
6312	12 VDC	6 A	A - D - W	15 l/min	2 bar	3/8" BSP (F)	2.5 kg	165x160x80
6314		11 A	Oil	6 l/min	4 bar		4.5 kg	185x240x85
6324	24 VDC	3 A	A - D - W	15 l/min	2 bar		2.5 kg	165x160x80
6326		6 A	Oil	6 l/min	4 bar		4.5 kg	185x240x85