



TUBOMATIC V450 ES

Code: TUBV450H6ES - TUBV450H8ES

CRIMPING (HIGH VOLUME CRIMPING) - 扣压机 (批量生产扣压机)

IDEAL FOR BIG FLANGES
适合大口径法兰



MAIN FEATURES - 主要特点



ES4 touch-screen electronic control on mobile support

ES4数控触摸屏
支持电子移动端控制



Self-lubricating moving components

自润滑



Silent pump

静音泵



Narrow crimping head for big flanges and 90° fittings

超薄扣压头
便于大法兰及
90°接头



Back limit switch

后接触式扣压装置



Protractor for fittings orientation

角度刻度盘



Service counter

保养提示



Industrial hose crimp calculator

工业管扣压
尺寸辅助计算



Ideal for volume production

适合批量加工

TECHNICAL DATA - 技术参数			
	TUBV450H6ES	TUBV450H8ES	
CRIMPING FORCE 扣压力	660 TON	830 TON	
6 SPIRALS 2 PIECES 6层	3"	3"	
INDUSTRIAL HOSE 工业管	16"	16"	
MAX Ø 扣压后最大尺寸	450 mm	450 mm	
DIE OPENING 模具张开量	Ø +180 mm	Ø +180 mm	
OPENING WITHOUT DIES 无模具张口量	560 mm	560 mm	
STANDARD VOLTAGE 标准电压	375V-420V 50HZ 3PH	375V-420V 50HZ 3PH	
MOTOR POWER 电机功率	7.5 Kw A=14,39	11 Kw A=20,76	
DIMENSIONS LxWxH 尺寸LxWxH	2187x1720x1854 mm	2187x1720x1854 mm	
WEIGHT WITHOUT OIL 净重不含油	6172 Kg	6493 Kg	
OIL (NOT INCLUDED) 液压油 (不包含)	300 lt	300 lt	
POWER PACK LxWxH 动力站LxWxH	925x680x1268 mm	925x680x1268 mm	
POWER PACK WEIGHT 动力站质量	395 Kg	395 Kg	

ACCESSORIES - 附件 (可选项)	
CRIMPING THROUGH PRESSURE CONTROL (INCLUDED) 压力设定系统 (包含)	INDUSTRY 4.0 KIT 工业4.0
CRIMPING SPEED CONTROL SYSTEM 压力速度控制系统	CRIMPING DIAMETER SELF CORRECTION 扣压尺寸自动校准
QUALITY CHECK: PRESSURE AND DIAMETER COMBINED CONTROL (INCLUDED) 质量检测系统: 压力与尺寸配合控制 (包含)	DATA SAVE ON CSV FILE CSV 格式数据存储
MULTISTEP CRIMPING DIAMETERS 多尺寸设定系统	
BARCODE 条形码	
CAMERA 摄像头	
CONNECTION TO PC 连接电脑	
DISPENSER + STANDARD QUICK CHANGE 发散式模具柜 + 标准的快速切换工具	
ELECTRIC PEDAL 脚踏板	
FRONT AND REAR PROTECTION NET WITH ACTIVATION LIMIT SWITCH 前后带电子开关的保护网	
SIDE HOLDER TABLE 侧支撑台	

Diameter (mm) 模具尺寸 (mm)	10	12	14	16	19	22	25	29	34	38	42	46	50	54	58	63	69	73	77	86	96	103	106	111	116	121	126	131	136	146	156	166	178	190	205	220	235	250	270	290	350				
	DIES LENGTH (mm) / 模具长度																																												
TUBV450H6ES	60	60	60	60	60	60	60	60	70	70	85	85	120	120	120	120	120	120	120	120	120	120	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145		
TUBV450H8ES	60	60	60	60	60	60	60	60	70	70	85	85	120	120	120	120	120	120	120	120	120	120	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145	145

* SPECIAL DIES BETWEEN Ø 290 AND 350 MM UPON REQUEST
* 根据需求可定制 290到 350 mm 之间的特殊模具

ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED - 所有标注的加工范围取决于所使用的接头类型

Product specifications could be modified without prior notice.

产品说明如有更改, 恕不另行通知。