




Titac T-120 Gen2 is our premium air stapler for industrial use

With its robust construction, high quality components and smooth operation, the T-120 Gen 2 is made to last and perform even in the most demanding conditions.

Accepts all of our current composite TU-staples and T-nails



Features

- Diffused rear exhaust keeps noise levels down and doesn't stir up dust.
- Low weight and minimal recoil makes it an ergonomic tool that can be used for hours on end.
- Low maintenance required: a couple of drops of oil every day or ten drops every week.



PLASA FASTENING

Plasa Fastening AB Verkstadsgatan 16 73338 Sala, Sweden Tel: +46-(0)224-19191 Email: info@plasafastening.com Web: www.plasafastening.com

Technical data

Weight	1.1 kg (2.4 lb)
Dimensions	226 x 150 x 44 mm (8.9" x 5.9" x 1.7")
	7–16 mm (1/4"–1/2") 75 staples (T-12: 65 T-nails)
Rec. pressure Max pressure	5 — 6 bar (72—87 psi) 7 bar (100 psi)
Air consumption	0.2 litre (0.007 cf) per driving operation at 6 bar operating pressure
Vibration level	Vibration below the limit of declaration according to EN 792-13 measured according to ISO 8662-11



Removable cover plate for easy access to the staple chute

Authorized reseller