

Size	mm	200
Axis of rotation	./.	horiz.
Load capacity	kg	230
Max. revolutions per minute	U/min.	120
Bearing diameter	mm	190 x 130
Max. center bore diameter	mm	40
Unit weight	kg	170
Max. tilting moment at the axis of rotation	Nm	2.500
Max. axial load	N	10.000
Max. mass moment of inertia	kgm ²	20
Max. tangential torque with clamping actuated	Nm	2.500
Max. tangential torque without clamping	Nm	270
Clamping type	./.	hyd.
Max. clamping pressure	bar ü	100
Dividing accuracy with direct mounted encoder	"	+/- 3
Repeatability	"	+/- 1
Concentricity of the pilot diameter	mm	0,01
Plain parallelism inklusiv Taumel	mm	0,01

Size	mm	355
Axis of rotation	./.	horiz.
Load capacity	kg	650
Max. revolutions per minute	U/min.	50
Bearing diameter	mm	300 x 200
Max. center bore diameter	mm	80
Unit weight	kg	310
Max. tilting moment at the axis of rotation	Nm	3.200
Max. axial load	N	12.800
Max. mass moment of inertia	kgm ²	76
Max. tangential torque with clamping actuated	Nm	1.800
Max. tangential torque without clamping	Nm	620
Clamping type	./.	hyd.
Max. clamping pressure	bar ü	120
Dividing accuracy with direct mounted encoder	"	+/- 3
Repeatability	"	+/- 1
Concentricity of the pilot diameter	mm	0,01
Plain parallelism inklusiv Taumel	mm	0,01