

T5

COMPACT ALL-ROUNDER

TESTED ACCORDING TO

- » EN ISO 13849
- » EN 60204-32
- » EN 62061
- » EN 62745
- » DNV



Thanks to its balanced proportions, the T5 transmitter can be equipped with a variety of operating elements and information sources. The freely programmable GDC-3.5 colour graphic display can easily be integrated.

TECHNICAL DATA

PROTECTION CLASS	IP 65
TEMPERATURE RANGE	-20 to +60 °C
WEIGHT	approx. 1800 g
DIMENSIONS	290 x 180 x 155 mm (W/D/H)
FREQUENCY RANGE	432-481/863-930 MHz; 2.4 GHz
BATTERY TECHNOLOGY	exchangeable, NiMH or Li-Ion
OPERATING TIME	up to 20 hours
OPERATING RANGE	> 100 m

OPTIONS

- STOP Cat. 3 PLe / SIL3
- Safe digital control functions up to Cat. 3 PLe / SIL3
- Safe analogue control functions up to Cat. 3 PLe / SIL3
- LED feedback
- 2.1" graphic display
- 2.8" graphic display
- 3.5" colour graphic display, freely programmable via Qt
- Keypad with 6 soft keys and 4 LEDs (RG)
- Video transmission from up to 4 cameras in real time
- Brightness sensor
- Tilt sensor
- Presence sensor
- Vibration alarm
- Control panel lighting
- Cable control with optional charging function
- CAN cable control
- Multi-operation
- User-defined switch-off time
- Customised labelling
- Bottom housing available in red, blue or grey
- Shoulder hook
- Shoulder cross belt
- Belly belt
- Neck belt

