

T6

EXTREMELY FLEXIBLE

TESTED ACCORDING TO

- » EN ISO 13849
- » EN 60204-32
- » EN 62061
- » EN 62745
- » DNV



The T6 transmitter is the perfect companion for demanding environments. Its housing offers space for up to 4 standard joysticks or 8 linear levers. The versatile transmitter can be customised with toggle switches, rotary switches, potentiometers and much more. The innovative displays of the GDM and GDC series can be accommodated in this housing variant.

TECHNICAL DATA

PROTECTION CLASS	IP 65
TEMPERATURE RANGE	-20 to +60 °C
WEIGHT	approx. 1900 g
DIMENSIONS	325 x 180 x 165 mm (W/D/H)
FREQUENCY RANGE	432-481/863-930 MHz; 2.4 GHz
BATTERY TECHNOLOGY	exchangeable, NiMH or Li-Ion
OPERATING TIME	up to 20 hours
OPERATING RANGE	> 100 m

OPTIONS

- STOP Cat. 3 PLe / SIL3
- Safe digital control functions up to Cat. 3 PLe / SIL3
- Safe analogue control functions up to Cat. 3 PLe / SIL3
- LED feedback
- 2.1" graphic display
- 2.8" graphic display
- 3.5" colour graphic display, freely programmable via Qt
- Keypad with 6 soft keys and 4 LEDs (RG)
- Video transmission from up to 4 cameras in real time
- Brightness sensor
- Tilt sensor
- Presence sensor
- Vibration alarm
- Control panel lighting
- Cable control with optional charging function
- CAN cable control
- Multi-operation
- User-defined switch-off time
- Customised labelling
- Bottom housing available in red, blue or grey
- Shoulder hook
- Shoulder cross belt
- Belly belt
- Neck belt

