

# Rittal – The System.

Faster – better – everywhere.

## Courtesy light – SZ 4139.140

Date : May 6, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Courtesy light – SZ 4139.140



## Product description

<b>Supply includes:</b>	Courtesy light Light Light cover Assembly parts
-------------------------	--

<b>Packs of:</b>	1 pc(s).
------------------	----------

<b>EAN:</b>	4028177092327
-------------	---------------

<b>Customs tariff number:</b>	94054095
-------------------------------	----------

<b>eCl@ss 5.1:</b>	27189241
--------------------	----------

<b>eCl@ss 7.0:</b>	27189241
--------------------	----------

<b>ETIM 6.0:</b>	EC000321
------------------	----------

## Product features

<b>Design:</b>	without door operated switch
----------------	------------------------------

<b>Dimensions:</b>	Width: 452 mm Height: 117 mm Depth: 50 mm
--------------------	---

<b>Rated operating voltage:</b>	100 V - 240 V, 1~, 50 Hz/60 Hz
---------------------------------	--------------------------------

<b>Installation options:</b>	TS horizontal section of the roof frame: direct
------------------------------	---

TS, SE vertical section: with TS adaptor bracket  
SE sections at the front and rear of the roof frame: with TS adaptor bracket  
SE extrusions at the side of the roof frame: direct  
AE, CM, TP: with universal bracket  
AE: with rail for interior installation

<b>Operating temperature:</b>	Operation (environment): -15°C...+45°C Bearing: -20°C...+70°C
<b>Power consumption:</b>	14 W
<b>Equipment (electrical):</b>	Ballast: Wide-range electronic ballast Light: Fluorescent lamp, base G13 Jack/socket (type): D, earthing-pin (type F, CEE 7/4) Switch (type): Integral, on/off/door-operated switch mode
<b>Rated insulation voltage:</b>	500 V DC/3.75 A
<b>Rated impulse withstand voltage, phase to earth:</b>	1000 V AC
<b>Rated impulse withstand voltage, phase to phase:</b>	500 V AC
<b>Light – installation type:</b>	Screw-fastening
<b>Light cover:</b>	yes
<b>Weight/pack:</b>	1.6 kg