



- MATERIAL
- 1 - Inner beam : Steel
  - 2 - Intermediate beam : Steel
  - 3 - Outer beam : Steel
  - 4 - Bearing  $\phi 10-\phi 4$  : Steel
  - 5 - Ball cages : Steel
  - 6 - End stop : Plastic

- SURFACE FINISH : Zinc plating
- WEIGHT : 13.5 Kg/m
- OPTIONS :

Different slide lengths, extension, surface finish,  $\phi$  and holes centres to customer's requirement.

**!** DO NOT DISMOUNT THE SLIDE !

Do not modify the slides !

- Dimensions in mm  
\* Loads indicated for a pair of slides

- Load in a major axis
- Load in a minor axis

- Results given according to our load testing protocol ( www.chambrelan.com )

Production according our general manufacturing tolerances (www.chambrelan.com/1016)

RA9	STEEL	
	17.03.2015	

L	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000	1050	1100	1150	1200	1300	1400	1500	1600	1700	1800	1900	2000	
D	275	315	375	415	475	515	575	615	675	715	775	815	875	915	975	1015	1075	1115	1175	1215	1315	1415	1515	1615	1715	1815	1915	2015	
Load* (Kg)	230	300	355	395	430	440	435	430	425	410	400	385	375	360	350	340	320	300	285	275	245	210	175	150	130	110	85	60	
Deflexion (mm)	5	5	5	5	5	6	6	6	6	6	7	7	8	8	8	8	9	10	10	10	10	10	10	10	13	14	16	20	22
Load* (Kg)	150	150	150	150	150	150	140	130	120	110	100	90	85	80	75	70	65	60	57	54	47	44	40	35	30	25	17	10	
Deflexion (mm)	8	8	9	10	12	15	16	17	18	20	21	23	24	25	27	28	29	31	32	33	36	39	42	45	48	52	56	60	

In a constant effort of improvement, the company reserves the right to modify its products without notice. No contractual information.