

## CLOSED SETTling TANK

REF: CVC – DC - TC



### Application:

- Suspended solids (SS or MES) removal.

### Characteristics:

- Salher brand, model CVC-DC-TC.
- Manufactured in Glass Fiber Reinforced Polyester (GFRP) with orthophthalic resins.
- Suspended solids removal efficiency: 65-70%.
- Organic matter removal efficiency: 30-35% BOD<sub>5</sub>.
- Geometric form: a cylinder with an inverted cone bottom.
- Center-feed chamber and Thompson V-notch weir.
- PVC inlet and outlet pipes.
- Outlet in the manhole to install a ventilation pipe.

2



φD	CENTRAL CYLINDER [mm]				PARTIAL MEASUREMENTS [mm]								CAPACITY
	φd1	φd2	φd3	E	h1	h2	H	c1	c2	c3	c4	LITERS	
1.000	75	75	300	700	800	500	1.563	100	150	300	750	750	
1.200	75	75	300	700	800	600	1.720	100	150	300	1.000	1.130	
1.400	90	90	300	700	800	700	1.870	100	150	300	1.200	1.590	
1.700	90	90	400	900	1.000	850	2.300	150	200	300	1.400	2.910	
2.000	110	110	500	900	1.000	1.000	2.530	150	200	300	1.700	4.190	
2.500	160	160	620	1.000	1.200	1.250	3.110	250	250	350	2.000	7.930	
3.000	160	160	690	1.200	1.400	1.500	3.700	250	250	350	2.500	13.420	
3.500	200	200	750	1.400	1.600	1.750	4.265	250	300	400	3.000	21.000	
4.000	200	200	1.000	1.600	1.800	2.000	4.840	250	300	400	3.500	30.980	