



FT-88-911-TP

BACKLIT KEYBOARD WITH INTEGRATED TOUCHPAD

The FT-88-911-TP is designed for vehicle mount in emergency, police, service, transport trucks and marine vessels. With a full-travel keystroke, the FT-88-911-TP feels like a regular keyboard while maintaining the rugged standards of all iKey products. Ideal for in-vehicle use, the FT-88-911-TP features red LED backlit keys for low-light environments, a one-touch emergency key and an integrated touchpad. Features 12 Function Keys 88-Key Functionality Integrated Backlighting Integrated Touchpad Mobile Mounting Holes One-Touch Emergency Key

Product Code FT-88-911-TP

| | |
|-------------------|--|
| CERTIFICATIONS | UL60950, CE, FCC Part 15, Class B, NEMA 4 |
| SHOCK | 3x11 ms pulses of 50g on each of 3 axes |
| CABLE | LENGTH: 4 ft coiled (1.2m) DESIGN: Swappable PS/2-Y (providing separate keyboard and mouse connections), or Single-Cable USB |
| KEY SWITCH | MATERIAL: ABS Polycarbonate plastic LIFE: Greater than 10 million cycles TRAVEL: 0.120 in. (3.0mm) ACTUATION FORCE: 2.20 oz +/- 0.18 oz (62.39g +/- 5g) FEEDBACK: Tactile with mechanical snap |
| VIBRATION | POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2kHz DURATION OF TEST PER AXIS: 3 hours |
| POWER | PS2: KEYBOARD: 315mA@5V (from Keyboard port) TOUCHPAD: 10mA@5V (from Mouse port) USB: 325mA@5V (from CPU port) |
| COMPATIBILITY | PS/2 KEYBOARD/TOUCHPAD: All Windows Operating Systems USB KEYBOARD/TOUCHPAD: All Windows and Macintosh OS |
| TEMPERATURE RANGE | Storage -40C to +90C (-40F to +194F) Operating -40C to +70C (-40F to +158F) |
| WEIGHT | 2.25 lbs +/- 0.10 lbs (1.02 kg +/- 0.05 kg) |
| WARRANTY | 1 Year Limited Warranty |
| HUMIDITY | 100% |
| DIMENSIONS | 11.94" x 7.69" x 1.20" (w-h-d) 303.3mm x 195.3mm x 30.5mm |
| MODEL NUMBERS | FT-88-911-TP-PS2: With PS/2 cable FT-88-911-TP-USB: With USB cable |